## This Page Is Inserted by IFW Operations and is not a part of the Official Record

### BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):


- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

### IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problems Mailbox.

A13

1/14



PRIOR ART

FIGURE



### 2/14






FIGURE 2




- A Max channel, no correlation
- B Min channel, no correlation
- C Max channel, complete correlation
- D Min channel, complete correlation (not present)
- Z Baseline 1:1






- A Max channel, polarisation diversity, full polarisation conversion
- B Min channel, polarisation diversity, full polarisation conversion
- E Max channel, pol'n diversity, no polarisation conversion
- F Min channel, pol'n diversity, no polarisation conversion
- Z Baseline 1:1

Figure 4







P' —— 2:2 SNR = 0dB
Q' —— 2:2 SNR = 6dB
R' —— 2:2 SNR = 12dB
S' —— 2:2 SNR = 18dB
T' —— 1:1 SNR = 0dB
U' —— 1:1 SNR = 6dB
V' —— 1:1 SNR = 12dB
W' —— 1:1 SNR = 18dB

FIGURE 6




Figure 7 - Capacity for 2:2 space diversity MIMO system with the basestation antennas (transmitter) completely correlated and the mobile completely uncorrelated.






Figure 8 - Capacity for 2:2 polarisation diversity MIMO with no polarisation conversion in the environment





and polarisation diversity configurations.

FIGURE 10.






FIGURE 11




FIGURE 12






FIGURE 13




FIGURE 14.






Fig 15 A




Fig 15B




FIGURE 16





FIGURE 17





FIGORE 18.

# Basic Space-Time Coding Techniques

Space-Time Block Coding (STBC)

• defined for 3G





Fincoder (n) Encoder (1) Information bits in

Layered Space-Time

more applicable to


(BLAST)

fixed/nomadic

11/14 Information bits out ž Decoder

> Space-Time Trellis Coding (STTC)

 suitable for both mobile and fixed






Figure 19

## Feedback STC - Separated Subchannels




Figure 20




Figure 21



14/14




FIGURE 22